

F117

Underwing Nozzle

BASIC

9.25LB

NOTE: Modifications below may be combined together with F117 except as noted.

- A Adds Ground Cable
- B Adds Vacuum Breaker
- C Replaces Bicycle Handle with Stirrup Type Handles - Don't use with K
- F Adds 2 1/2" ANPT Female Inlet (No Swivel) - Add to F117, A, B, C, D, J, K, MY, MZ, Y and Z only
- G Adds 45 PSI HECV - Don't use with F, H, L or P
- H Adds 35 PSI HECV - Don't use with F, G, L or P
- J Replaces Standard Outlet Connector with Replaceable Wear Points
- K Replaces Standard Handle with 13" Long Handle - Don't use with C
- L Adds 50 PSI HECV - Don't use with F, G, or H
- M Adds Pressure Gauge - Don't use with MY, MZ, Y or Z
- N Adds F116 Type Nose Seal
- P Adds 55 PSI HECV - Don't use with F, G, H, or L
- Q Adds 45 degree MS Flange Adapter
- T Adds Applicable 40-Mesh Strainer to Mate Coupling Ordered - Don't use with F, U, or V
- U Adds Applicable 60-Mesh Strainer to Mate Coupling Ordered - Don't use with F, T, or V
- V Adds Applicable 100-Mesh Strainer to Mate Coupling

Ordered - Don't use with F, T, or U

W Adds MS Flange Adapter

X Adds reinforced nose section

The following modifications are independent of each other but may be combined with others listed above except F, Q, and W.

3A Adds (3") Coupling and Swivel F584AL, 2 1/2" NPT

3B Adds (3") Coupling and Swivel F584BL, 2 1/2" BSPPL

3C Adds (3") Coupling and Swivel F584CL, 3" NPT

3D Adds (3") Coupling and Swivel F584DL, 2" NPT

3E Adds (3") Coupling and Swivel F584EL, 3" BSPPL

4A Adds (3") Coupling and Dry Disconnect 2 1/2" NPT

4B Adds (3") Coupling and Dry Disconnect 2 1/2" BSPPL

4C Adds (3") Coupling and Dry Disconnect 3" NPT

4D Adds (3") Coupling and Dry Disconnect 2" NPT

4E Adds (3") Coupling and Dry Disconnect 3" BSPPL

7A Adds (2 1/2") AL Coupling and Swivel F582AE, 2 1/2" NPT

7B Adds (2 1/2") AL Coupling and Swivel F582BE, 2 1/2" BSPPL

7C Adds (2 1/2") AL Coupling and Swivel F582CE, 3" NPT

7D Adds (2 1/2") AL Coupling and Swivel F582DE, 2" NPT

3, 4 Adds 3" Alum. Coupling with Replaceable Cres Wire Races

5 Adds 2 1/2" Brass Coupling Mate with Flight Refuel Swivel

7

Adds 2 1/2" Alum. Coupling with Replaceable Cres
Wire Races